

Serving Science, Technology, Labs & Engineering Sectors Worldwide.

EN ISO 3696 laboratory water provides cost-effective purified water for general laboratory support functions such as washing, rinsing and equipment feed, where reduced hardness, dissolved solids and microbial load are required. It is not intended for analytical measurements or for the preparation of reagents, buffers or culture media.

Typical application are research and teaching laboratories, clinical support, hospital sterilisation units and in pharmaceutical, cosmetics, food and beverage and industrial quality control.

Each batch undergoes rigorous quality control and is produced in accordance with EN ISO 3696:1995 specifications.

PARAMETER / GRADE	1	2	3
pH @ 25° C Including range	Not applicable	Not applicable	5 to 7.5
Conductivity mS/m Max	0.01	0.1	0.5
Oxidizable matter mg/L max	Not applicable	0.08	0.4
Absorbance at 254nm and 1 cm Optical path length absorbance units Max	0.001	0.01	Not specified
Residue on evaporation after heating at 110° C mg/kg Max	Not applicable	1	2
Silica(SiO ₂) content mg/L Max	0.01	0.02	Not specified
CAS Number	7732-18-5		
Shelf Life	6 months when unopened and stored between 2°C and 18°C in a dark environment		

- ✓ **UK Manufacturer**
- ✓ **Fast - Just in time deliveries**
- ✓ **No Chemical Additives**
- ✓ **Extensive Formulated Range**
- ✓ **Batch Traceability**
- ✓ **Manufactured in ISO-certified purpose built facilities**

OPTIONS:

- ✓ **Application specific cap solutions**
- ✓ **In volumes to meet your needs from 100ml to 27,000L**
- ✓ **Ultrafast Emergency Service Available**

- ✓ **Custom Formulation Capability**
- ✓ **Nitrogen & Ozone Flushing**
- ✓ **Gamma Irradiation**
- ✓ **Non-Standard container types to suit your requirements**



Call or email to discuss your ultrapure water requirements

T. +44(0)1942 914 007 E. sales@waterson-scientific.co.uk W. www.waterson-scientific.co.uk
Unit 18, Heron Business Park, Tan House Lane, Widnes WA8 0SW

A Division of Waterson Ltd

